

Central Jersey Trailer & Hitch Depot Inc.

Phone: 9082031911
45 Fourth Street
Somerville, NJ
Email: sales@hitchone.com



2024 Homesteader Trailers 822HT Cargo / Enclosed Trailer

Stock#: 128698	Year: 2024	Manufacturer: Homesteader Trailers
Width: 102" or 8'6"	Length: 270" or 22'6"	Weight: 3400
GVWR: 14000	Payload: 10600	Color: WHITE
#Axles: 2		
URL: https://hitchone.com/2024-homesteader-trailers-822ht-cargo-enclosed-trailer-zTkq.html		

MSRP	\$14,400.00
Price	\$14,600.00

Features

- Manual Top Wind Jack	- 2 5/16 Coupler	- Adjustable Coupler
- Break away Switch	- Electric Brake(s)	- 8 Hole Wheels
- 235/80/R16 TIRES	- BLACK MOD WHEELS 16"	- Rubber Torsion Suspension
- 60" TONGUE, TRIPLE TUBE	- 12" ON CENTER FLOOR	- BEAVER TRAILER
- 7-Way Plug	- Insulated Wire Harness	- LED Lighting
- DOT Approved Lighting	- BACK UP LIGHTS LED	- E-TRACK DOWN BOTH WALLS
- 8 RECESSED D-RINGS 5,000LBS EACH	- BLACK OUT TRIM PACKAGE	- 32" SIDE DOOR
- HD REAR RAMP DOOR	- EXTENDED FLAP ON RAMP DOOR	- 3/4" PLYWOOD WALLS IPO 3/8"

Description

Hercules 8.5' Wide Enclosed Trailers

The Hercules 8.5 enclosed cargo trailer series of trailers is larger and more advanced than ever with its line of 8.5 enclosed wide bumper pulls and 8.5 enclosed wide gooseneck trailer models.

To construct the most durable, most dependable enclosed trailers around we begin from the ground up. For the smoothest and most comfortable ride, the Hercules 8.5 is constructed of rubber torsion axles with E-Z lube hubs along with radial tires.

For the strongest most dependable enclosed trailers we use 2x6 tube steel to construct our main frame. To insure support we place floor crossmembers and tubular wall posts 16" O.C. In the interior we add a 3/4" exterior grade plywood flooring and a 3/8" premium plywood sidewall liner.

For style and performance the Hercules 8.5 enclosed cargo trailer has a sleek aerodynamic body with .030 gauge

aluminum with a baked on enamel finish.

Standard specifications include a 102" body, 96" interior width, 81 1/2" between the wheel wells, and an interior height of 6'8". Backed behind every Hercules 8.5 enclosed utility trailer is a 3 year limited manufacturer's warranty.

The Hercules 8.5 enclosed utility trailer can be equipped with over 100 options in order to suit your trailer needs. Options include side doors in various sizes, ramp with spring assist, roof vents, flow through vents, aluminum treadplate stoneguard, Vee-nose front, extra height, air conditioning, aluminum treadplate flooring, aluminum corners, aluminum wheels, and various other options too numerous to tell.

Standard Features

2x6 Tube Steel Main Frame

Under Coated Frame

Full Height Crossmembers

Tubular Wall Studs 16" O.C.

Independent Suspension Torsion Axles

11 Year Manufactured Limited Warranty on Torsion Axles

EZ Lube Hubs

Modular-Styled Wheels

Trailer Rated Radial Tires

Aluminum Fender Flares

Break-Away Kit with Battery, and Charger

Complete LED Lighting

5K Tongue Jack

Safety Chains

.030 Aluminum Exterior With Baked Enamel Finish

High Tech Self-Leveling Roof Sealant

Seamless Aluminum Roof

Aerodynamic Styling

Aerodynamic TPO (Thermo-Plastic Poly-Olefin) Nosecap

Long Life Coated Fasteners

Automotive Style Weatherstripping

Semi-Trailer Style Fastener Bars with Zinc-Coated Finish

Keyed Lockable Door Hasp

Door Hold Back Chains

Door Grab Handles

Premium 3/8" Plywood Wall Liner

3/4" Exterior Grade Plywood Floor

Interior Light

3 Year Limited Structural Warranty

Floor Crossmember Full Height 16" O.C.

2x6 Tube Steel Outriggers 16" O.C.

96" Interior Width

6'8" Interior Height

82" Between Wheel Wells

86" Door Opening Width

72" Door Opening Height

D.O.T. Compliant Lighting

D.O.T. Compliant Conspicuity Tape

Brakes on All Wheels

Primed and Painted Frame

Aluminum Door Hold Back

5" Exterior Fastener Pattern

NATM Certified

Popular Options

Side Entry Door Fluorescent Light Air Conditioner White Aluminum Wall Liner White Vinyl Ceiling Liner Aluminum Treadplate Floor Concession Door Solid Rear Wall 30x20 Window Chrome Wheels Aluminum Wheels 48" Escape Door Awning Ladder Racks Dome Light Porch Light 500 Watt Recessed Halogen Light Rear Ramp Door w/ Cable Assist Aluminum Treadplate on Ramp Door Transition Plate Adjustable Coupler Caster Wheel for Tongue Spare Tire and Wheel Spare Tire Compartment Rear Stabilizer Jacks Front ATP Stone Guard D-Ring Tie Downs Roof Vents 16 x 96 Overhead and Base Cabinets V-nose with Chrome Point Chrome Corners Wrapped Rear Structure Extra Sidewall Height Flow Thru Sidewall Vents (Pair) 3/4" Plywood 2' high on sidewalls Flushlock -- Side Door Wall Mount E-Track Floor Mount E-Track Strap For E-Track with Ratchet Wall Mount D-Rings Luan Ceiling Liner Nosecap & Rear Header Enclosure (Liner Rqd.)

Insulated Ceiling (Liner Required) Insulated Walls Black / White Checkered Vinyl Floor Black/White Checkered Vinyl -- Ramp and Flap Black Marble Vinyl -- Ramp and Flap Black Marble Vinyl Floor 60" Tongue IPO Standard 15 Amp 110V Motorbase Plug 30 Amp Breaker Box 110V w/ Lifeline 110V Receptacle (Interior) 110V Receptacle w/ GFI (Exterior) 110V Light Switch(Interior) 36x24 Generator Door 40x32 Generator Door 36x24 Generator Box Insulated without Door 40x32 Generator Box Insulated without Door Seven Colors to choose from Enclosed Landing Gear *** Occasionally it may become necessary to produce Homesteader products with different components or processes than initially specified. All such changes are approved for use by Homesteader in order to maintain the quality standards associated with the Homesteader name. All illustrations and specifications contained in this web site are based on the latest product information at time of publication. We assume no responsibility for any error in type or print reproduction of specifications in the web site. Homesteader reserves the right to make changes in prices, colors, materials, equipment, specifications, and processes and to discontinue models or options at any time without notice. For more information or to purchase Challenger enclosed cargo trailers visit your nearest authorized Homesteader Dealer.*

null